

ADJUSTABLE X-RAY TABLE X-Ray Table with electric height and tilt adjustment



Product description:

Our x-ray tables with electric height and tilt adjustment have been specially developed for use in the X-ray specialty field. One of their main features is the absence of longitudinal brace at the front of the leg frame, allowing the free positioning of a C-arm.

The radiolucent table surface has a thickness of 15 mm (for table width 650 mm) or 25 mm (for table width 800 mm).

The size of the metal-free area is 1430 x 600 mm (LxW).

The X-ray tables feature dual electric anodized aluminium lifting columns controlled by low-voltage, ultra-quiet electric motors and a hand switch.

Specifications for each motor: 230V, 50/60Hz, 2,0A, 120W, IP20, v=16mm/s, 1000N.

For enhanced stability, the leg frame is equipped with levelling screws.

Options :

One-piece tabletop / or

Two-piece tabletop with headrest positively adjustable by grid.

As a standard feature, the headrest is placed on the right hand side. The table is also available with a headrest on the left hand side, upon request at time of order.

Mobility :

The X-ray tables are also available in a mobile version, with :

Castors, Ø 75 mm
 Castors, Ø 125 mm
 A set includes four castors, two of which are lockable.

Central locking castor system
 for enhanced maneuverability and comfort of use.
 All four double castors (Ø 125 mm) are connected by rods. A foot pedal to lock in position or release is located at the head and foot ends of the table.

Note: With castors, the overall height of the table will change (650-900 / 700-950 mm). Please contact us for more information.

Accessories :

In order to equip the table with accessories such as

Infusion (IV) Pole
 Side safety rail
 Armrest/Arm support
 The standard rails are available in different lengths :

Standard rails, length 400 mm
 Standard rails, length 600 mm
 Standard rails, length 1000 mm
 Standard rails, length 1400 mm
 Standard rails, length 1700 mm
 The position of the standard rails, whether at the head, feet or in the middle, may be specified at time of order.

Upholstered pads for better patient comfort :
 To provide a additional comfort for the patient while lying position, we recommend the optional 40 mm-thick upholstered pads. The pads are easily attached onto the upper frame of the table by hook and loop closures. See your selection of 21 available upholstery colours.

Upholstery pad, width 65 cm
 Upholstery pad, width 80 cm

Technical info :

Height adjustment range 550 - 800 mm (Low-voltage electric motors with hand switch)
 Widths - 650 mm / 800 mm
 Length - 1900 mm
 One-piece or two-piece tabletop
 Maximum load - 150 kg
 Product weight - 90 kg
 Frame - lacquered

Frame :

The colour coating of the frame is available as a standard in three different colours :

light grey (RAL 7035),
 white aluminium (RAL 9006),
 pure white (RAL 9010).

The high-quality paint has a glossy finish, is easy to clean and resistant to disinfectants.

Upholstery color: Without upholstered pad, White, Birch, Yellow, Mandarin, Rosewood, Red, Old pink, Magenta, Sky Blue, Baltic, Atoll, Blue, Almond, Turquoise, Green, Purple, Light grey, Grey, Anthracite, Black, Conductive black,

Brown

Frame color : RAL 7035, RAL 9010, RAL 9006

Wheel: Without wheels, With - Ø 75 mm, With - Ø 125

Upholstered pad options: Without upholstered pad, With - 190 x 65 cm, With - 190 x 80 cm

Tabletop: One piece tabletop, Two pieces tabletop

Reference: -