


FUJIFILM FCR PRIMA T2

This compact table-top reader unit has outstandingly high-speed processing capability to challenge the common misconception of CR



Product description:

High-speed processing

FCR PRIMA T2 is a table-top reader unit which boasts a world-class high processing speed of 73 IPs/hour. In the high speed mode (5 pixels/mm), throughput is enhanced almost 70% compared with FCR PRIMA T (only for IPs of 14" x 17" and 14" x 14"). As with all Fujifilm equipment FCR PRIMA T2 is easy to operate. It will help reduce patient waiting time and greatly increase the efficiency of examination workflow.

Space-saving design

FCR PRIMA T2, with its light and compact table top design, can be placed on a desk, shelf or anywhere space is limited. As this is a fully digital reader, neither a darkroom nor automatic processor is required. FCR PRIMA T2 can always be installed in the space formally used by a chemistry based processor.

Stable high-quality images

Although this is a compact machine its excellent image quality is the same as that produced by the rest of the FCR range. Image Intelligence™, Fujifilm's proprietary image processing technology, enhances image contrast and sharpness, without any deterioration of details. FCR PRIMA T2 supports accurate diagnosis by offering stable and optimized image quality.

Specifications

Standard components	FCR PRIMA T2 Image reader (Model : CR-IR 392)
Applicable console	FCR PRIMA T2 Console, FCR View; CR Console, Console Advance
Main Connectable Imagers	DryPix PRIMA/Smart/Lite/Plus/4000

Supplies	<p>Plaque d'imagerie ST-VI: 35 x 43 cm (14 "x 17"), 35 x 35 cm (14 "x 14"), 10 "x 12", 8 "x 10", 24 x 30 cm, 18 x 24 cm, 15 x 30 cm Type de cassette IP CC: 35 x 43 cm (14 "x 17"), 35 x 35 cm (14 "x 14"), 10 "x 12", 8 "x 10", 24 x 30 cm, 18 x 24 cm, 15 x 30 cm</p>
Time required for IP Feed/Load	Min. 49 sec.
Processing capacity	Up to 73 IPs/hr
Reading specification	10 pixels / mm, 5 pixels / mm
Time to start on display	Min. 33 sec.
Time to print on DryPix Prima	Approx. 165 sec. (Approx. 155 s) * in case of 35 x 43 cm (14 "17")
Number of stacker	1
Network	10 Base T / 100 Base TX
Dimensions (W x D x H)	560 x 540 x 392 mm (22" x 21" x 15")
Weight	39 kg (86 lbs.)
Power supply conditions	Single phase 50-60 Hz AC120 - 240 V +-10% 1.9A (max)
Environnemental conditions	<p>Operating conditions</p> <ul style="list-style-type: none"> • Temperature: 15-30 ° C • Humidity: 15 to 80% HR (no dew condensation) • Atmospheric pressure: 750-1060hPa

Reference: -