

X-RAY LEADED MOBILE SHIELDS MAVIG WD204
Mobile protection screen with leaded glass



Product description:

Working in radiation exposed environment requires appropriate protection. Therefore this mobile shield combines upper and lower body protection. The modular mobile shield, available in different widths, consists of an upper section with transparent lead glass and a lower shield part. We offer the mobile shield with a lead equivalent value of Pb 0.50 mm or Pb 2.00 mm.

- The lead glass has excellent light transmission
- Light weight aluminum frame construction
- Lead equivalent shield: Pb 0.50 mm or Pb 2.00 mm (other Pb values on request)
- Lead equivalent window: Pb 2.00 mm
- Overall widths: 700 to 1600 mm / 27.6 to 63.0 in (in steps of 100 mm / 3.9 in)
- Overall height: 1950 mm / 76.8 in

Dimensions of the lead glass window:

- W x H: 360 x 460 mm / 14.2 x 18.1 in (for widths of the mobile shield from 700 to 800 mm / 27.6 to 31.5 in)
- W x H: 460 x 460 mm / 18.1 x 18.1 in (for widths of the mobile shield from 900 to 1100 mm / 35.4 to 43.3 in)
- W x H: 560 x 460 mm / 22.0 x 18.1 in (for width of the mobile shield of 1600 mm / 63.0 in)
- W x H: 660 x 460 mm / 26.0 x 18.1 in (for widths of the mobile shield from 1400 to 1500 mm / 55.1 to 59.1 in)
- W x H: 760 x 460 mm / 29.9 x 18.1 in (for width of the mobile shield of 1600 mm / 63.0 in)

Lead equivalent: 0.50 mm Pb, 2 mm Pb

Reference: Mav-WD204